

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Clock Settings

External Clock
Rate (MHz)
+/- 20ppm
155.52

Standard Protocol

Bit Rate (Gbps)

Clock Source:  **Internal**

Clock Rate:

Must attach external clock of appropriate rate if this option is selected.

 External

10GE LAN

10.3125

161.1328



RX Derived

10.70922532

G.709

167.3316

Start Load Save Save JPG Print Exit



Apply Now

SONET TrojanCOL		LOF	DOF	AISL	RDIL	REIL	AISIP	RDIP	REIP	B1	B2	B3	Reser.	00:00:02:27 Elapsed Time (DD:HH:MM:SS)		
Instance: BERT Setup		BER 1E-07		Gate Type A to B		Time 0		Actual Time		Actual Totals Hz Rate Gate Control		Start	Stop	Reset	RX Count B2R1 RX ESSR1 RX ESRT	
Out	-9.00 dBm	-6.70 dBm	0.00 dBm	1550 nm	None Optical Decade	TX clock	ON	ON	TX Source	Non OUT	Actual Power	-6.70 dBm	0.00 dBm	0.00 dBm	1550 nm	9.00 dBm
HELP		ADMIN		localhost		Status		11:38:33AM Wed 10 Sep 2003								